



R-T表

广东爱晟电子科技有限公司

R25	30(KΩ)	阻值精度	1.0%	型号: DT303F3936AEQ			
B25/50	3936K	B值精度	1.0%				
Temp(°C)	Rmin(KΩ)	Rnor(KΩ)	Rmax(KΩ)	Temp(°C)	Rmin(KΩ)	Rnor(KΩ)	Rmax(KΩ)
-40	913.841	955.579	999.124	3	81.5086	83.1758	84.8686
-39	856.751	895.298	935.487	4	77.6322	79.1812	80.7529
-38	803.603	839.216	876.320	5	73.9616	75.4004	76.8595
-37	754.100	787.014	821.282	6	70.4847	71.8210	73.1752
-36	707.969	738.398	770.058	7	67.1904	68.4310	69.6876
-35	664.959	693.100	722.361	8	64.0679	65.2196	66.3853
-34	624.839	650.873	677.925	9	61.1075	62.1762	63.2573
-33	587.397	611.490	636.507	10	58.2999	59.2914	60.2936
-32	552.438	574.741	597.884	11	55.6364	56.5558	57.4847
-31	519.782	540.434	561.850	12	53.1089	53.9612	54.8217
-30	489.264	508.392	528.215	13	50.7096	51.4994	52.2962
-29	460.729	478.451	496.805	14	48.4315	49.1630	49.9005
-28	434.037	450.461	467.459	15	46.2678	46.9449	47.6271
-27	409.058	424.283	440.030	16	44.2122	44.8386	45.4693
-26	385.672	399.788	414.380	17	42.2586	42.8378	43.4206
-25	363.767	376.859	390.383	18	40.4016	40.9367	41.4748
-24	343.241	355.386	367.924	19	38.6358	39.1299	39.6263
-23	323.999	335.268	346.893	20	36.9563	37.4121	37.8698
-22	305.953	316.411	327.193	21	35.3585	35.7786	36.2001
-21	289.022	298.729	308.731	22	33.8380	34.2248	34.6127
-20	273.129	282.141	291.422	23	32.3906	32.7465	33.1029
-19	258.147	266.513	275.122	24	31.0125	31.3394	31.6667
-18	244.079	251.847	259.835	25	29.7000	30.0000	30.3000
-17	230.864	238.077	245.490	26	28.4250	28.7246	29.0244
-16	218.445	225.144	232.025	27	27.2110	27.5097	27.8089
-15	206.769	212.992	219.380	28	26.0550	26.3524	26.6504
-14	195.788	201.569	207.500	29	24.9539	25.2494	25.5459
-13	185.456	190.828	196.335	30	23.9047	24.1981	24.4927
-12	175.731	180.723	185.837	31	22.9048	23.1958	23.4881
-11	166.574	171.213	175.963	32	21.9517	22.2399	22.5296
-10	157.949	162.260	166.673	33	21.0428	21.3280	21.6149
-9	149.821	153.828	157.927	34	20.1761	20.4580	20.7419
-8	142.159	145.884	149.692	35	19.3492	19.6277	19.9083
-7	134.934	138.397	141.934	36	18.5602	18.8351	19.1122
-6	128.118	131.337	134.624	37	17.8071	18.0783	18.3518
-5	121.686	124.679	127.732	38	17.0883	17.3556	17.6253
-4	115.614	118.396	121.233	39	16.4018	16.6652	16.9311
-3	109.880	112.466	115.102	40	15.7462	16.0055	16.2674
-2	104.463	106.867	109.316	41	15.1199	15.3751	15.6330
-1	99.344	101.579	103.854	42	14.5215	14.7724	15.0262
0	94.505	96.583	98.696	43	13.9495	14.1962	14.4459
1	89.931	91.862	93.824	44	13.4027	13.6452	13.8907
2	85.604	87.398	89.221	45	12.8799	13.1181	13.3593

**R-T表**

广东爱晟电子科技有限公司

R25	30(KΩ)	阻值精度	1.0%	型号: DT303F3936AEQ			
B25/50	3936K	B值精度	1.0%				
Temp(°C)	Rmin(KΩ)	Rnor(KΩ)	Rmax(KΩ)	Temp(°C)	Rmin(KΩ)	Rnor(KΩ)	Rmax(KΩ)
46	12.3800	12.6138	12.8508	89	2.6257	2.7167	2.8106
47	11.9017	12.1313	12.3640	90	2.5416	2.6305	2.7223
48	11.4441	11.6694	11.8979	91	2.4604	2.5473	2.6371
49	11.0062	11.2272	11.4514	92	2.3822	2.4671	2.5548
50	10.5870	10.8037	11.0238	93	2.3068	2.3898	2.4755
51	10.1840	10.3965	10.6123	94	2.2340	2.3151	2.3990
52	9.7981	10.0063	10.2180	95	2.1638	2.2431	2.3251
53	9.4284	9.6325	9.8399	96	2.0961	2.1736	2.2537
54	9.0742	9.2741	9.4775	97	2.0308	2.1065	2.1848
55	8.7348	8.9306	9.1298	98	1.9677	2.0418	2.1183
56	8.4095	8.6012	8.7964	99	1.9069	1.9792	2.0541
57	8.0976	8.2853	8.4765	100	1.8482	1.9189	1.9921
58	7.7986	7.9823	8.1696	101	1.7914	1.8606	1.9321
59	7.5118	7.6917	7.8750	102	1.7367	1.8043	1.8742
60	7.2368	7.4128	7.5923	103	1.6838	1.7499	1.8183
61	6.9729	7.1451	7.3209	104	1.6328	1.6973	1.7642
62	6.7197	6.8882	7.0602	105	1.5834	1.6465	1.7120
63	6.4767	6.6415	6.8099	106	1.5358	1.5974	1.6614
64	6.2435	6.4047	6.5694	107	1.4897	1.5500	1.6126
65	6.0196	6.1773	6.3384	108	1.4452	1.5042	1.5654
66	5.8046	5.9588	6.1165	109	1.4022	1.4598	1.5197
67	5.5982	5.7489	5.9031	110	1.3606	1.4170	1.4755
68	5.3999	5.5473	5.6981	111	1.3205	1.3756	1.4328
69	5.2094	5.3534	5.5010	112	1.2816	1.3355	1.3915
70	5.0263	5.1672	5.3114	113	1.2440	1.2967	1.3515
71	4.8504	4.9881	5.1292	114	1.2077	1.2592	1.3128
72	4.6813	4.8159	4.9539	115	1.1726	1.2229	1.2753
73	4.5188	4.6503	4.7852	116	1.1386	1.1878	1.2391
74	4.3625	4.4911	4.6230	117	1.1057	1.1538	1.2040
75	4.2123	4.3379	4.4668	118	1.0738	1.1209	1.1700
76	4.0677	4.1905	4.3165	119	1.0430	1.0891	1.1371
77	3.9287	4.0487	4.1719	120	1.0132	1.0583	1.1052
78	3.7950	3.9122	4.0326	121	0.9844	1.0285	1.0744
79	3.6663	3.7808	3.8985	122	0.9565	0.9996	1.0445
80	3.5424	3.6543	3.7694	123	0.9294	0.9716	1.0155
81	3.4245	3.5339	3.6464	124	0.9032	0.9445	0.9875
82	3.3111	3.4180	3.5280	125	0.8779	0.9182	0.9603
83	3.2018	3.3063	3.4138	126	0.8533	0.8928	0.9340
84	3.0966	3.1987	3.3038	127	0.8296	0.8682	0.9085
85	2.9953	3.0951	3.1978	128	0.8065	0.8443	0.8837
86	2.8977	2.9952	3.0957	129	0.7842	0.8211	0.8597
87	2.8037	2.8990	2.9972	130	0.7626	0.7987	0.8365
88	2.7131	2.8062	2.9022	131	0.7416	0.7770	0.8139

